



GTCL-TMFL



GLOBAL TECH CO-ORD LTD 280A Whitton Avenue East Greenford Middx UB6 0JP London
United Kingdom

Tel: +44 20 3475 6819
Fax: +44 20 3475 6829

Email: info@globaltcltd.com
Web: www.globaltcltd.com



ENGINE	Speed	1500/1800 RPM
	Fuel	Diesel
	Origin	EU/Japan
	Cooling System	Water
	No. of Cylinders	3/4
	Induction System	Naturally Aspirated
	Injection System	Indirect
	Cycles	4
	Electric System	12 VDC
	Governor	Mechanical

ALTERNATOR	Type	Synchronous
	Frequency	50/60 Hz
	Excitation	Brushless
	Insulation Class	H
	Protection Class	IP23

GLOBAL TECH CO-ORD LTD 280A Whitton Avenue East Greenford Middx UB6 0JP London
United Kingdom

Tel: +44 20 3475 6819

Fax: +44 20 3475 6829

Email: info@globaltcltd.com

Web: www.globaltcltd.com



CANOPY	Produced of Steel Sheets
	Protects system against all weather conditions
	Designed to minimize noise
	All doors are equipped with locks
	Door with window in front of control panel to observe instruments
	Fine design to enable insufficient air circulation
	Spacious interior enables easy maintenance and service
	Electrostatic powder coated
	Heavy-duty, robust structure

CONTROL PANEL & ATS	Voltmeter		Ammeter	
	Control Module		Start-Stop Key	
			Digital Frequency Display	
			Protection for Low Oil Pressure	
			Protection for high temperature	
			Protection for high/low Speed	
			Protection for Low Fuel	
	Visible and Audible Alarm W/ automatic stop mechanism			
	Hour meter	Fuel level gauge	Main CB and CB's for lamps	
	Emergency Stop Button			

GLOBAL TECH CO-ORD LTD 280A Whitton Avenue East Greenford Middx UB6 0JP London
United Kingdom

Tel: +44 20 3475 6819

Fax: +44 20 3475 6829

Email: info@globaltcltd.com

Web: www.globaltcltd.com



TRAILOR	Single axle, 13"-15" wheels, in compliance with Directive 2009/40/EC
	Rolled Steel construction, heavy-duty robust structure
	Torsion suspension system suitable for rough terrain
	8 hours daily fuel tank in trailer frame complete with float, draining cap, filling
	Self-rotating towing hook with spring suspension
	Jockey wheel w/ adjustable height under tow bar
	Three retractable support jacks with adjustable height

MAST & LIGHTS	Hydraulic/Electric/Pneumatic	
	Mast Direction	Vertical
	Mast Height	7.70 Meters
	Type	Galvanized Telescopic Section
	Stabilizers	4 Adjustable Manual Stabilizers
	Lifting System	Hydraulically lifting system
	Wind stability	100 Km/h
	Light Tilt System	Electric tilt system for flood lights
	Flood Lights	6 x 1000W or 4 x 1500W Metal Halide Square/round Total 660,000 Lumens
	Rotation	340 °

Above specifications are for reference only. GTCL has the authority to change the catalog without notice.

GLOBAL TECH CO-ORD LTD 280A Whitton Avenue East Greenford Middx UB6 0JP London
United Kingdom

Tel: +44 20 3475 6819

Fax: +44 20 3475 6829

Email: info@globaltcltd.com

Web: www.globaltcltd.com